



/

AirMEDIA-D Indoor				
	2.9mm*	3.9mm*	5.2mm*	7.8mm*
	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD
	112,896 56,448 /m ²	65,536 32,768 /m ²	36,864 18,432 /m ²	16,384 8,192 /m ²
	250 × 500	250 × 500	250 × 500	250 × 500
	500 × 1000 × 80*	500 × 1000 × 80*	500 × 1000 × 80*	500 × 1000 × 80*
	2 × 2	2 × 2	2 × 2	2 × 2
	84 × 168	64 × 128	48 × 96	32 × 64
	168 × 336	128 × 256	96 × 192	64 × 128
	10.7 kg/ *	10.7 kg/ *	10.7 kg/ *	10.7 kg/ *
	16 panels	16 panels	16 panels	16 panels
	-90°~+90°;	-90°~+90°;	-90°~+90°;	-90°~+90°;
			IP30	IP30
	1000nits	1000nits	1000nits	1000nits
	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz
	160°	160°	160°	160°
	140°	140°	140°	140°
	14 - 16 bit	14 - 16 bit	14 - 16 bit	14 - 16 bit
	281 trillion	281 trillion	281 trillion	281 trillion
	4,000 : 1	4,000 : 1	4,000 : 1	4,000 : 1
	288 w/m ²	288 w/m ²	288 w/m ²	288 w/m ²
	640 w/m ²	640 w/m ²	640 w/m ²	640 w/m ²
	-10 ~ 40 °C/ 10% ~ 80%	-10 ~ 40 °C/ 10% ~ 80%	-10 ~ 40 °C/ 10% ~ 80%	-10 ~ 40 °C/ 10% ~ 80%
	-20 ~ 60°C / 10% ~ 90%	-20 ~ 60°C / 10% ~ 90%	-20 ~ 60 °C/ 10% ~ 90%	-20 ~ 60 °C/ 10% ~ 90%
	100,000 Hrs	100,000 Hrs	100,000 Hrs	100,000 Hrs
	CE, EMC,FCC,ETL	CE, EMC,FCC,ETL	CE, EMC,FCC,ETL	CE, EMC,FCC,ETL

:



/

door)					
	2.6mm*	2.9mm*	3.9mm	4.8mm	5.2mm
	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD	3-in-1 SMD
	147,456 /m ² 36,864 /	112,896 /m ² 56,448 /	65,536 /m ² 32,768 /	43,264 /m ² 21,632 /	36,864 /m ² 18,432 /
	250 × 250	250 × 500	250 × 500	250 × 500	250 × 500
	500 × 1000 × 80*	500 × 1000 × 80*	500 × 1000 × 80*	500 × 1000 × 80	500 × 1000 × 80
	2 × 2	2 × 2	2 × 2	2 × 2	2 × 2
	96 × 96	84 × 168	64 × 128	52 × 104	48 × 96
	192 × 192	168 × 336	128 × 256	104 × 208	96 × 192
	11.2 kg/ *	11.2 kg/ *	11.2 kg/ *	11.2 kg/	11.2 kg/
	16 panels	16 panels	16 panels	16 panels	16 panels
	-90°~+90°;	-90°~+90°;	-90°~+90°;	-90°~+90°;	-90°~+90°;
	IP 65	IP 65	IP 65	IP 65	IP 65
	4000nits	4000nits	4500nits	5000nits	5000nits
	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz
	140°	140°	140°	140°	140°
	120°	120°	120°	120°	120°
	14 - 16 bit	14 - 16 bit	14 - 16 bit	14 - 16 bit	14 - 16 bit
	281 trillion	281 trillion	281 trillion	281 trillion	281 trillion
	4,000 : 1	4,000 : 1	4,000 : 1	4,000 : 1	4,000 : 1
	246 w/m ²	246 w/m ²	246 w/m ²	246 w/m ²	246 w/m ²
	736 w/m ²	736 w/m ²	736 w/m ²	736 w/m ²	736 w/m ²
	-30 ~ 50 °C/ 10% ~ 90%	-30 ~ 50 °C/ 10% ~ 90%	-30 ~ 50 °C/ 10% ~ 90%	-30 ~ 50 °C/ 10% ~ 90%	-30 ~ 50 °C/ 10% ~ 90%
	-30 ~ 60 °C/ 10% ~ 95%	-30 ~ 60 °C/ 10% ~ 95%	-30 ~ 60 °C/ 10% ~ 95%	-30 ~ 60 °C/ 10% ~ 95%	-30 ~ 60 °C/ 10% ~ 95%
	100,000 Hrs	100,000 Hrs	100,000 Hrs	100,000 Hrs	100,000 Hrs
	CE, EMC,FCC,ETL	CE, EMC,FCC,ETL	CE, EMC,FCC,ETL	CE, EMC,FCC,ETL	CE, EMC,FCC,ETL

:



door)			
		7.8mm*	10.4mm*
		3-in-1 SMD	3-in-1 SMD
		16,384 /m ² 8,192 /	9,216 /m ² 4,608 /
		250 × 500	250 × 500
		500 × 1000 × 80	500 × 1000 × 80
		2 × 2	2 × 2
		32 × 64	24 × 48
		64 × 128	48 × 96
		11 kg/	11 kg/
		16 panels	16 panels
		-90°~+90°;	-90°~+90°;
	IP 65	IP 65	IP 65
		5000nits	5000nits
		1,920 -3840 Hz	3,840 Hz
		140°	140°
		120°	120°
		14 - 16 bit	14 - 16 bit
		281 trillion	281 -2.5n panels12T061/
		3,000 : 1	
		246 w/m ²	
		736 w/m ²	
		-30 ~ 50 °C / 10% ~ 90%	
		-30 ~ 60 °C / 10% ~ 95%	
		100,000 Hrs	

